

Universal Quattro LNB

Universal LNB with 4 separate outputs (low band V/H, high band V/H)

Convertitore universale a 4 uscite separate (banda bassa V/H, banda alta V/H)

Universal LNB mit 4 separaten Ausgängen (unteres Band V/H, oberes Band V/H)

Specifications | Caratteristiche tecniche | Technische Spezifikationen

- **Frequency range** | Frequenza di ricezione | *Empfangsfrequenz* **10,7-12,75 GHz**
- **L.O. Frequency** | Oscillatori locali (LOF) | *Lokalszillatorfrequenz (LOF)* **9,75 / 10,6 GHz**
- **Noise figure** | Cifra di rumore | *Rauschmaß* **0,2 dB**
- **Conversion gain** | Guadagno | *Verstärkung* **55 dB low band, 67 dB high band**
- **Feed-diameter** | Diametro feed | *Feeddurchmesser* **40 mm**
- **DC current consumption** | Assorbimento | *Stromaufnahme* **max. 250 mA**
- **Pol. switching voltage** | Alimentazione | *Umschaltspannung* **10,5-19 V**

Art. LNB 105

Packing: carton box

Imballo: cartone

Einzelverpackung: Karton

Packing unit: 50 pcs.

Confezione: 50 pz.

Verpackungseinheit: 50 St.



Art. LNB 105 B

Packing: blister

Imballo: blister

Einzelverpackung: Blister

Packing unit: 60 pcs.

Confezione: 60 pz.

Verpackungseinheit: 60 St.

